

What is claimed is:

1. An apparatus for controlling a cache storing data,
said apparatus provided with key control protection using
5 a storage key for an access to data, said apparatus
comprising:
 - a demand device demanding the storage key;
 - a control device starting a retrieval of the data
in the cache without waiting for arrival of the demanded
10 storage key; and
 - a transfer device transmitting the retrieved data.
2. The apparatus according to claim 1, wherein
the transfer device transmits the retrieved data
15 without waiting for arrival of the demanded storage key.
3. The apparatus according to claim 1, further
comprising:
 - a translation lookaside buffer device
20 registering a correspondence relation between a logical
address and a physical address; and
 - an address translation device transforming the
logical address into the physical address, wherein
when a logical address of the access is not
25 registered in the translation lookaside buffer device,

the control device demands translation of the logical address of the access from the address translation device, registers the translation result in the translation lookaside buffer device, and retrieves the translation lookaside buffer device without waiting for arrival of the demanded storage key.

4. The apparatus according to claim 1, further comprising:

10 a translation lookaside buffer device registering a correspondence relation between a logical address and a physical address; and

an address translation device transforming the logical address into the physical address, wherein

15 when a logical address of the access is not registered in the translation lookaside buffer device, the control device demands translation of the logical address of the access from the address translation device, registers the translation result in the translation lookaside buffer device, and releases the address translation device without waiting for arrival of the demanded storage key.

5. The apparatus according to claim 4, further comprising a plurality of key access ports storing an

arrived storage key, wherein

the address translation device continuously transforms a plurality of logical addresses associated with a plurality of accesses, and the demand device
 5 demands a corresponding storage key each time translation completes.

6. The apparatus according to claim 1, wherein

the control device completes an access process for
 10 an access that does not require the key control protection, without waiting for arrival of the demanded storage key.

7. A cache control method used for a data processing device provided with key control protection using a
 15 storage key for an access to data, comprising:

searching a translation lookaside buffer for a logical address of the access;

transforming the logical address into a physical address when the logical address is not registered in
 20 the translation lookaside buffer device;

demanding the storage key;

registering a translation result of the logical address in the translation lookaside buffer;

searching the translation lookaside buffer again,
 25 without waiting for arrival of the demanded storage key;

and

transmitting data stored in a cache, corresponding to the logical address.

5 8. An cache control device used for a data processing device provided with key control protection using a storage key for an access to data, comprising:

 cache means for storing the data;

 demand means for demanding the storage key;

10 control means for starting a retrieval of the data in the cache means without waiting for arrival of the demanded storage key; and

 transfer means for transmitting the retrieved data.

15